

TUBO PTFE CORRUGADO

PTFE CONVOLUTED HOSE

CARACTERÍSTICAS:

Fabricado a partir de PTFE virgem (polytetrafluorethylene) ondulado, revestido a malha de inox AISI 304. Preparado para ser assembled com terminais hidráulicos.

TEMPERATURA DE TRABALHO:

-70°C / +260°C

TUBO: PTFE Corrugado

REFORÇO: 1 trança de aço inox AISI 304

CHARACTERISTICS:

Manufactured from virgin PTFE (polytetrafluorethylene) convoluted resin with AISI 304 stainless STEEL, high tensile braid. Assemble with hydraulic tail fittings.

OPERATING TEMPERATURE:

-70°C / +260°C

TUBE: Convoluted PTFE

REINFORCEMENT: 1 stainless steel braid AISI 304



REFERÊNCIA CODE	DIÂM. INTERNO INTERNAL DIAM.			EXTERIOR OUTSIDE		PRESSÃO SERVIÇO WORKING PRESSURE		MIN. RAIOS CURV. MIN. BEND RADIUS		PESO WEIGHT
	DN	mm	Pol./ Inch	mm	Pol./ Inch	Bar	PSI	mm	Pol./ Inch	
104300.04	6	6,4	1/4"	12,3	0,366	172	2494	18	0,708	-
104300.05	8	8,0	5/16"	12,3	0,484	138	2000	20	0,787	-
104300.06	10	9,7	3/8"	15,25	0,503	138	2000	20	0,787	-
104300.08	12	13,0	1/2"	18,8	0,700	103	1490	25	0,984	-
104300.10	16	16,0	5/8"	22,8	0,858	83	1200	51	2,007	-
104300.12	19	19,0	3/4"	24,65	1,236	69	1000	64	2,519	-
104300.16	25	25,4	1"	32,77	1,503	46	667	89	3,503	-
104300.20	31	31,8	1.1/4"	40,72	1,814	34	500	127	5,000	-
104300.24	38	38,1	1.1/2"	48,25	1,964	30	435	152	5,984	-
104300.32	51	50,8	2"	61,50	2,625	23	333	200	7,874	-