

MANGUEIRA ÓLEO S&D 10 Bar OIL S&D HOSE 10 Bar

CARACTERÍSTICAS:

Mangueira para sucção e trasfega de Óleo, e Carburantes até 50% de aromáticos.

TEMPERATURA DE TRABALHO: -30° C / + 100° C

TUBO: Interior em Nitrilo resistente a óleo.

REFORÇO: Reforço em tela têxtil, com helicoidal em aço.

COBERTURA: Exterior em Nitrilo resistente a abrasão e a condições atmosféricas.

RESISTÊNCIA AO VÁCUO: - 0.9 Bar

CHARACTERISTICS:

Special hose for delivery of oil, gasoline and diesel with up to 50% aromatic content.

OPERATING TEMPERATURE: -30°C to +100°C

TUBE: Black special Nitrile oil resistant rubber tube.

REINFORCEMENT: High tensile textile reinforcement with antistatic wire.

COVER: Black special Nitrile rubber cover - abrasion and weather resistant.

VACUUM RESISTANCE: - 0.9 Bar



REFERÊNCIA CODE	DIÂM. INTERNO INTERNAL DIAM.			EXTERIOR OUTSIDE		PRESSÃO SERVIÇO WORKING PRESSURE		PESO WEIGHT Kg/m
	DN	mm	Pol./ Inch	mm	Pol./ Inch	Bar	PSI	
102805.0006BF	6	6,4	1/4"	15	19/32"	10	145	0,200
102805.0008BF	8	7,9	5/16"	18	23/32"	10	145	0,225
102805.0010BF	10	9,5	3/8"	20	51/64"	10	145	0,285
102805.0012BF	12	12,7	1/2"	22	7/8"	10	145	0,350
102805.0016BF	16	15,9	5/8"	26	1" 1/32	10	145	0,436
102805.0019BF	19	19	3/4"	29	1" 5/32	10	145	0,620
102805.0022BF	22	22,2	7/8"	33	1" 19/64	10	145	0,700
102805.0025BF	25	25,4	1"	35	1" 3/8	10	145	0,700
102805.0028BF	28	28	1" 1/8	40	1" 7/64	10	145	0,770
102805.0030BF	30	30	1" 3/16	40	1" 37/64	10	145	0,800
102805.0032BF	32	32	1" 1/4	42	1" 21/32	10	145	0,900
102805.0035BF	35	35	1" 3/8	46	1" 13/16	10	145	1,050
102805.0038BF	38	38	1" 1/2	50	1" 31/32	10	145	1,200
102805.0040BF	40	40	1" 37/64	52	2" 3/64	10	145	1,250
102805.0045BF	45	45	1" 7/8	60	2" 3/8	10	145	1,700
102805.0050BF	50	51	2"	63	2" 1/2	10	145	1,700
102805.0055BF	55	55	2" 11/64	70	2" 3/4	10	145	1,950
102805.0060BF	60	60	2" 3/8	74	2" 15/16	10	145	1,980
102805.0063BF	63	63,5	2" 1/2	77	3" 1/32	10	145	2,100
102805.0076BF	76	76	3"	90	3" 35/64	10	145	2,700
102805.0080BF	80	80	3" 5/32	94	3" 45/64	10	145	2,850
102805.0100BF	100	102	4"	118	4" 41/64	10	145	4,100
102805.0127BF	127	127	5"	147	5" 13/16	10	145	6,100
102805.0150BF	150	152	6"	172	6" 13/16	10	145	7,800

MARCAÇÃO // MARKING:

