

MANGUEIRA ASPIRFLEX

ASPIRFLEX HOSE

CARACTERÍSTICAS:

Mangueira adequada para sucção e entrega de líquidos em aplicações industriais e agrícolas.

TEMPERATURA DE TRABALHO:

-15°C / +60°C

TUBO: Mangueira de PVC de alta flexibilidade suave.

REFORÇO: Espiral de aço galvanizado.

COBERTURA: Transparente.

ESPECIFICAÇÕES: A pedido: não tóxico e do tipo alimentar, de acordo com CE 1935/2004 - UE 10/2011 cat. A, B, C.

CHARACTERISTICS:

Hose suitable for suction and delivery of liquids in industrial and agricultural applications.

OPERATING TEMPERATURE:

-15°C / +60°C

TUBE: High flexible soft PVC hose.

REINFORCEMENT: Galvanized steel spiral.

COVER: Transparent

SPECIFICATIONS: On request: non-toxic and food type in according to CE 1935/2004 - UE 10/2011 cat. A, B, C.



REFERÊNCIA CODE	DIÂM. INTERNO INTERNAL DIAM.		PRESSÃO SERVIÇO WORKING PRESSURE		VÁCUO VACUUM	MIN. RAIO CURV. MIN. BEND RADIUS		PESO WEIGHT
	mm	Pol./ Inch	Bar	PSI	Bar	mm	Pol./ Inch	Kg/m
109100.010	10	0.393	8	116	8,5	24	0.944	0,18
109100.012	12	0.472	8	116	8,5	24	0.944	0,18
109100.014	14	0.551	8	116	8,5	30	1.181	0,21
109100.016	16	0.629	8	116	8,5	34	1.338	0,30
109100.020	20	0.787	7	102	8,5	50	1.968	0,33
109100.022	22	0.866	6	87	8,5	55	2.165	0,38
109100.025	25	0.984	6	87	8,5	60	2.362	0,51
109100.030	30	1.181	5	73	8,5	70	2.755	0,60
109100.032	32	1.259	5	73	8,5	75	2.952	0,68
109100.035	35	1.377	5	73	8,5	80	3.149	0,75
109100.038	38	1.496	5	73	8,5	90	3.543	0,80
109100.040	40	1.574	5	73	8,5	95	3.740	0,90
109100.045	45	1.771	5	73	8,0	110	4.330	1,15
109100.050	50	1.968	5	73	8,0	125	4.921	1,25
109100.060	60	2.362	5	73	8,0	140	5.511	1,80
109100.063	63	2.480	5	73	8,0	145	5.708	1,90
109100.075	75	2.952	4	58	7,0	200	7.874	2,30
109100.080	80	3.149	3	44	7,0	220	8.661	2,50
109100.090	90	3.543	3	44	7,0	260	10.236	3,00
109100.100	100	3.937	3	44	7,0	280	11.023	3,70
109100.102	102	4.015	3	44	7,0	280	11.023	3,70
109100.113	113	4.448	3	44	7,0	320	12.598	3,95
109100.150N	150	5.905	2	29	7,0	450	17.716	6,50
109100.0152	152	5.984	2	29	7,0	450	17.716	6,50